



Elegant Design  
 Fanless  
 Flexible Ergonomics

The POS-510 EyePOS GT III has the character of a stylish sports car. It is a POS system with the glass metal stand engineered by 4POS that shines without and convinces within. New completely fanless with increased graphics/processor performance and Powered USB.

With this series, 4POS has developed a compact all-in-one POS solution absolutely matchless in design. The POS terminal can be used freestanding on the counter, fixed at the check-out, mounted on the wall – it really couldn't be more flexible.



## All-in-One POS-510 EyePOS GT III



1. Slim Bezel touch



2. Standard configuration with unique EyeSTAND POS in metal glass construction



3. Optional 8.4" stand alone customer display



4. Optional VFD stand alone customer display



5. Optional 10.4" rear mount customer display



6. Rich I/O connector ports  
 - 4 x USB 3.0  
 - 2 x USB 2.0  
 - 2 x Powered USB  
 - 2 x COM Port



# POS-510 EyePOS GT III



Model Name		POS-510 EyePOS GT III
<b>Housing</b>		
Material	Die-cast Magnesium-Aluminium	
Mount	VESA 100	
<b>Mainboard</b>		
	D86U	
CPU	Intel Core i3-7100U / Intel Core i5-7200U	
Chipset / GPU	CPU Integrated / Intel HD Graphics DX 12	
System Memory	1 x DDR3L SO-DIMM up to 8GB	
<b>Display / Touch</b>		
Display Size	15" TFT LCD with LED backlight and Anti-Glare Coating	
Brightness	500 cd/m <sup>2</sup>	
Maximum Resolution	1024 x 768	
Touch Screen Type	Capacitive	
Tilt Angle (Degree)	30° Low Stand / 70° High Stand	
<b>Storage</b>		
Primary Device Bay	1 x 2.5 SATA (HDD or SSD)	
<b>External I/O Ports</b>		
USB	6 x USB (4 x USB 3.0 + 2 x USB 2.0)	
Powered USB	2 x USB (1 x 12V + 1 x 24V)	
Serial/COM	3 x COM ports with RJ-45 (5V/12 power selectable by BIOS)	
LAN	1x RJ-45 (10/100/1000 Mbit)	
VGA out	1 x D-Sub (15 pin) with Power over VGA (activated via BIOS)	
Cash Drawer	1 x RJ-11 with 12V or 24V	
Speaker	2 x 2W	
<b>Control/Indicator/Power</b>		
Power Button	1 (right side)	
Power Indicator	LED	
Power Supply	External, DC 19V (120W)	
<b>Environment</b>		
EMC & Safety	FCC, Class A, CE, LVD	
Operating Temperature	0° C ~ 35° C	
IP	IP54 sealed front panel with touch screen	
<b>Options</b>		
Second Display	10.4" TFT LED Display / VFD Display (2 x 20 characters)	
WLAN	802.11 a/b/g/n/AC mini PCI-E Wireless LAN Card + BT 4.0	
Magnetic Card Reader	3 tracks MSR (via USB)	
<b>Dimension (W x D x H)</b>		
Panel PC only	360 x 277 x 42 mm	
Panel PC with Low Stand	360 x 277 x 137 mm	
Panel PC with High Stand	360 x 277 x 276 mm	
<b>Weight</b>		
Panel PC only	3.1 kg	
Panel PC with Low Stand	4.8 kg	
Panel PC with High Stand	5.5 kg	
<b>Colour</b>		
	Black	
<b>OS Support</b>		
	Windows 10 (64bit), Windows 10 IoT Enterprise (64bit), Linux	

V1908

Notes: Specifications are subject to change without notice. Product photos and pictures are for illustration purposes only and may differ from the real product's appearance.

